

Swage flagpoles are made of 2 or more tubes of 50mm diameter joined together by putting one into another

Flag display:
 The flag display depends on gusts of wind.



Flag fixing:
 rope and hooks
 (attached to the flag)

Hoisting and lowering of the flag:
 using an external rope fixed to the belying cleat mounted 1,5m above the ground

TUBE PROFILE:
 Swage aluminum

ANODIZING:
 20 microns

WALL THICKNESS:
 2 mm

AVAILABLE ACCESSORIES

FINIALS		WEIGHT [kg]
1	Plastic cap	0,06
2	Rotating truck head	0,21
3	Golden bulb/round finial (brass)	0,22
4	Silver bulb/round finial (aluminum)	0,16
5	Black mushroom shaped top (plastic)	0,142
6	Aluminum flat top fi 75	0,185



HALYARD SYSTEM		WEIGHT [kg]
1	Rope (polyester or polypropylene)	0,008 /mb
2	Belying cleat	0,026



INSTALLATION ELEMENT		WEIGHT [kg]
1	Steel zinced hear shaped base For car tire	3,4
2	Steel zinced round base for usage with extra ballast	6,15
3	Aluminum ground sleeve 50mm For foundation	0,4
4	Steel zinced base for screwing into the ground For installation in soil (ground, mud, sand)	1,48
5	Steel powder coated base for hammering into the ground For installation in soil (ground, mud, sand)	1,5
6	Steel zinced cross base For installing in ground using anchors or using pavement bricks as an extra ballast	4,6



Height [m]	3	4,5	6
Number of sections [pcs]	2	3	4
Flagpole diameter (top/bottom) [mm]	50	50	50
Net weight without accessories [kg]	2,7	3,9	5,2
Recommended size of the flag [m]	1,2 x 2 [2,4 m ²]	1,2 x 2 [2,4 m ²]	1,2 x 2 [2,4 m ²]
Size of transport package [cm] ±5%	190x11x6	190x11x11	190x11x11